

Revision Date: 09/16/2014 Date of issue: 09/16/2014 Supersedes Date: 02/12/2013

Version: 1.0

SECTION 1: IDENTIFICATION

Product Identifier

Product Name: KELLY'S® Z.O.E. IMPRESSION PASTE

Product Code: 011350-000 **Intended Use of the Product**

Designed for use in the preparation of full or partial denture impressions in a custom tray or as a wash. Type II Medium-Bodied.

Name, Address, and Telephone of the Responsible Party

Company

Water Pik, Inc.

1730 East Prospect Road Fort Collins, CO 80553-0001 800/525-2020 (8 am- 4pm MST) **Emergency Telephone Number**

Emergency Number: 800/424-9300 (24 Hr: CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2 H315 Eye Irrit. 2A H319 Skin Sens. 1 H317 STOT RE 2 H373 Aquatic Acute 1 H400 Aquatic Chronic 1 H410

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US)





Signal Word (GHS-US) : Warning

Hazard Statements (GHS-US) : H315 - Causes skin irritation.

H317 - May cause an allergic skin reaction.

H319 - Causes serious eye irritation.

H373 - May cause damage to organs through prolonged or repeated exposure.

H400 - Very toxic to aquatic life.

H410 - Very toxic to aquatic life with long lasting effects.

Precautionary Statements (GHS-US): P260 - Do not breathe vapors, mist, spray.

P264 - Wash hands, forearms, and exposed areas thoroughly after handling. P272 - Contaminated work clothing must not be allowed out of the workplace.

P273 - Avoid release to the environment.

P280 - Wear protective clothing, protective gloves, eye protection.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P314 - Get medical advice/attention if you feel unwell.

P321 - Specific treatment (see Section 4).

P333+P313 - If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 - If eye irritation persists: Get medical advice/attention. P362+P364 - Take off contaminated clothing and wash it before reuse.

P391 - Collect spillage.

EN (English US) 09/16/2014 1/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

P501 - Dispose of contents/container according to local, regional, national, territorial, provincial, and international regulations.

Other Hazards

Exposure may aggravate those with pre-existing eye, skin, or respiratory conditions. Inhalation of dusts and fumes can cause metal fume fever. Symptoms can include a metallic or sweet taste in the mouth, sweating, shivering, headache, throat irritation, fever, chills, thirstiness, muscle aches, nausea, vomiting, weakness, fatigue, and shortness of breath.

Unknown Acute Toxicity (GHS-US) Not available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Name	Product Identifier	% (w/w)	Classification (GHS-US)
Zinc oxide	(CAS No) 1314-13-2	0.1 to 1, 1 to 5, 5 to 10, 10 to 30,	Aquatic Acute 1, H400
		30 to 60, or 60 to 88	Aquatic Chronic 1, H410
Talc	(CAS No) 14807-96-6	0.1 to 1, 1 to 5, 5 to 10, 10 to 30,	Comb. Dust
		or 30 to 40	STOT RE 2, H373
Rosin, polymerized	(CAS No) 65997-05-9	0.1 to 1, 1 to 5, 5 to 10, 10 to 30,	Not classified
		or 30 to 35	
Eugenol	(CAS No) 97-53-0	0.1 to 1, 1 to 5, 5 to 10, or 10 to 15	Acute Tox. 4 (Oral), H302
			Eye Irrit. 2A, H319
			Skin Sens. 1, H317
Cottonseed oil	(CAS No) 8001-29-4	0.1 to 1, 1 to 5, 5 to 10, or 10 to 13	Not classified
Fatty acids, linseed-oil	(CAS No) 68424-45-3	0.1 to 1, 1 to 5, or 5 to 7	Not classified
Petrolatum	(CAS No) 8009-03-8	0.1 to 1, 1 to 5, or 5 to 7	Not classified
Paraffin waxes and Hydrocarbon waxes	(CAS No) 8002-74-2	0.1 to 1 or 1 to 4	Comb. Dust
Olive oil	(CAS No) 8001-25-0	0.1 to 1 or 1 to 3	Not classified
Acetic acid	(CAS No) 64-19-7	0.1 to 1	Flam. Liq. 3, H226
			Skin Corr. 1A, H314
			Eye Dam. 1, H318
			Aquatic Acute 3, H402

More than one of the ranges of concentration prescribed by Controlled Products Regulations has been used where necessary, due to varying composition.

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

General: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

Inhalation: When symptoms occur: go into open air and ventilate suspected area. Keep at rest and in a position comfortable for breathing. Call a POISON CENTER or doctor/physician if you feel unwell.

Skin Contact: Remove contaminated clothing. Drench affected area with water for at least 15 minutes. Wash contaminated clothing before reuse. Obtain medical attention if irritation persists. Wash with plenty of soap and water.

Eye Contact: Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. Obtain medical attention if irritation persists.

Ingestion: Rinse mouth. Do NOT induce vomiting.

Most Important Symptoms and Effects Both Acute and Delayed

General: Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause damage to organs through prolonged or repeated exposure.

Inhalation: May cause respiratory irritation. Inhalation of fumes may cause metal fume fever.

Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Eye Contact: Causes serious eye irritation.

Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: Repeated or prolonged inhalation may damage lungs.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

09/16/2014 EN (English US) 2/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Use extinguishing media appropriate for surrounding fire.

Unsuitable Extinguishing Media: Do not use a heavy water stream. A heavy water stream may spread burning liquid.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not flammable.

Explosion Hazard: Product is not explosive.

Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Exercise caution when fighting any chemical fire. **Firefighting Instructions:** Use water spray or fog for cooling exposed containers.

Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection. Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Hazardous Combustion Products: Irritating fumes. Oxides of zinc and carbon. Hydrocarbons. If heated to the point of fume generation zinc fumes may cause metal fume fever.

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: Avoid all contact with skin, eyes, or clothing. Avoid breathing vapor, mist, or spray. Do not allow product to spread into the environment.

For Non-Emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).

Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Personnel

Protective Equipment: Equip cleanup crew with proper protection.

Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters. Avoid release to the environment.

Methods and Material for Containment and Cleaning Up

For Containment: As an immediate precautionary measure, isolate spill or leak area in all directions. Avoid generation of dust during clean-up of spills.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely. Contact competent authorities after a spill.

Reference to Other Sections

See heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Additional Hazards When Processed: Any proposed use of this product in elevated-temperature processes should be thoroughly evaluated to assure that safe operating conditions are established and maintained.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work. Wash contaminated clothing before reuse.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep container closed when not in use.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Specific End Use(s) Designed for use in the preparation of full or partial denture impressions in a custom tray or as a wash. Type II Medium-Bodied.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Zinc oxide (1314-13-2)			
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m ³	

09/16/2014 EN (English US) 3/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

	7, No. 30 / Worlday, Waren 20, 2012 / Naies And	
USA ACGIH	ACGIH STEL (mg/m³)	10 mg/m ³
USA OSHA	OSHA PEL (TWA) (mg/m³)	5 mg/m ³
USA NIOSH	NIOSH REL (TWA) (mg/m³)	5 mg/m ³
USA NIOSH	NIOSH REL (STEL) (mg/m³)	10 mg/m ³
USA NIOSH	NIOSH REL (ceiling) (mg/m³)	15 mg/m ³
USA IDLH	US IDLH (mg/m³)	500 mg/m ³
Alberta	OEL STEL (mg/m³)	10 mg/m ³
Alberta	OEL TWA (mg/m³)	2 mg/m ³
British Columbia	OEL STEL (mg/m³)	10 mg/m ³
British Columbia	OEL TWA (mg/m³)	2 mg/m ³
Manitoba	OEL STEL (mg/m³)	10 mg/m ³
Manitoba	OEL TWA (mg/m³)	2 mg/m ³
New Brunswick	OEL STEL (mg/m³)	10 mg/m ³
New Brunswick	OEL TWA (mg/m³)	5 mg/m ³
Newfoundland & Labrador	OEL STEL (mg/m³)	10 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	2 mg/m ³
Nova Scotia	OEL STEL (mg/m³)	10 mg/m ³
Nova Scotia	OEL TWA (mg/m³)	2 mg/m ³
Nunavut	OEL STEL (mg/m³)	10 mg/m ³
Nunavut	OEL TWA (mg/m³)	10 mg/m³ (total mass)
Northwest Territories	OEL STEL (mg/m³)	10 mg/m ³
Northwest Territories	OEL TWA (mg/m³)	10 mg/m³ (total mass)
Ontario	OEL STEL (mg/m³)	10 mg/m³
Ontario	OEL TWA (mg/m³)	2 mg/m³
Prince Edward Island	OEL STEL (mg/m³)	10 mg/m³
Prince Edward Island	OEL TWA (mg/m³)	2 mg/m³
Québec	VECD (mg/m³)	10 mg/m³
Québec	VEMP (mg/m³)	5 mg/m ³
Saskatchewan	OEL STEL (mg/m³)	10 mg/m³
Saskatchewan	OEL TWA (mg/m³)	2 mg/m ³
Yukon	OEL STEL (mg/m³)	20 mg/m³
Yukon	OEL TWA (mg/m³)	10 mg/m³
	OLL TWA (IIIg/III)	10 mg/ m
Talc (14807-96-6) USA ACGIH	ACCILL T\A/A /mag/m3\	2 mg/m³
	ACGIH TWA (mg/m³)	
USA NIOSH	NIOSH REL (TWA) (mg/m³)	2 mg/m³ (containing no Asbestos and <1% Quartz)
USA IDLH	US IDLH (mg/m³)	1000 mg/m³ (containing no asbestos and <1% quartz)
Alberta	OEL TWA (mg/m³)	2 mg/m³
British Columbia	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica)
Manitoba	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and <1% Crystalline silica)
New Brunswick	OEL TWA (mg/m³)	2 mg/m ³
Newfoundland & Labrador	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and
	(g/)	<1% Crystalline silica)
Nova Scotia	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and
A	OEL TMA / 22	<1% Crystalline silica)
Nunavut	OEL TWA (mg/m³)	6 mg/m³ (total mass)
Northwest Territories	OEL TWA (mg/m³)	6 mg/m³ (total mass)
Ontario	OEL TWA (mg/m³)	2 mg/m³ (containing no Asbestos and <1% Crystalline silica)
Prince Edward Island	OEL TWA (mg/m³)	2 mg/m³ (particulate matter containing no Asbestos and
	, , ,	1 0 11

09/16/2014 EN (English US) 4/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Transfer of the contract of th	7, No. 58 / Monday, March 26, 2012 / Rules And	<1% Crystalline silica)		
Outhor	\/FNAD /mag/ma3\	3 mg/m ³		
Québec Saskatchewan	VEMP (mg/m³) OEL TWA (mg/m³)			
Yukon		2 mg/m³		
11				
Paraffin waxes and Hydroca	· · · · · · · · · · · · · · · · · · ·	2 1/3		
USA ACGIH	ACGIH TWA (mg/m³)	2 mg/m³		
USA NIOSH	NIOSH REL (TWA) (mg/m³)	2 mg/m³		
Alberta	OEL TWA (mg/m³)	2 mg/m³		
British Columbia	OEL TWA (mg/m³)	2 mg/m³		
Manitoba	OEL TWA (mg/m³)	2 mg/m³		
New Brunswick	OEL TWA (mg/m³)	2 mg/m³		
Newfoundland & Labrador	OEL TWA (mg/m³)	2 mg/m³		
Nova Scotia	OEL TWA (mg/m³)	2 mg/m³		
Nunavut	OEL STEL (mg/m³)	6 mg/m ³		
Nunavut	OEL TWA (mg/m³)	2 mg/m³		
Northwest Territories	OEL STEL (mg/m³)	6 mg/m³		
Northwest Territories	OEL TWA (mg/m³)	2 mg/m³		
Ontario	OEL TWA (mg/m³)	2 mg/m³		
Prince Edward Island	OEL TWA (mg/m³)	2 mg/m³		
Québec	VEMP (mg/m³)	2 mg/m³		
Saskatchewan	OEL STEL (mg/m³)	4 mg/m³		
Saskatchewan	OEL TWA (mg/m³)	2 mg/m³		
Yukon	OEL STEL (mg/m³)	6 mg/m ³		
Yukon	OEL TWA (mg/m³)	2 mg/m ³		
Acetic acid (64-19-7)				
USA ACGIH	ACGIH TWA (ppm)	10 ppm		
USA ACGIH	ACGIH STEL (ppm)	15 ppm		
USA OSHA	OSHA PEL (TWA) (mg/m³)	25 mg/m ³		
USA OSHA	OSHA PEL (TWA) (ppm)	10 ppm		
USA NIOSH	NIOSH REL (TWA) (mg/m³)	25 mg/m ³		
USA NIOSH	NIOSH REL (TWA) (ppm)	10 ppm		
USA NIOSH	NIOSH REL (STEL) (mg/m³)	37 mg/m ³		
USA NIOSH	NIOSH REL (STEL) (ppm)	15 ppm		
USA IDLH	US IDLH (ppm)	50 ppm		
Alberta	OEL STEL (mg/m³)	37 mg/m ³		
Alberta	OEL STEL (ppm)	15 ppm		
Alberta	OEL TWA (mg/m³)	25 mg/m ³		
Alberta	OEL TWA (ppm)	10 ppm		
British Columbia	OEL STEL (ppm)	15 ppm		
British Columbia	OEL TWA (ppm)	10 ppm		
Manitoba	OEL STEL (ppm)	15 ppm		
Manitoba	OEL TWA (ppm)	10 ppm		
New Brunswick	OEL STEL (mg/m³)	37 mg/m ³		
New Brunswick	OEL STEL (ppm)	15 ppm		
New Brunswick	OEL TWA (mg/m³)	25 mg/m³		
New Brunswick	OEL TWA (ppm)	10 ppm		
Newfoundland & Labrador	OEL STEL (ppm)	15 ppm		
Newfoundland & Labrador	OEL TWA (ppm)	10 ppm		
Nova Scotia	OEL STEL (ppm)	15 ppm		
Nova Scotia	OEL TWA (ppm)	10 ppm		
Nunavut	OEL STEL (mg/m³)	39 mg/m ³		

09/16/2014 EN (English US) 5/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Nunavut	OEL STEL (ppm)	15 ppm
Nunavut	OEL TWA (mg/m³)	26 mg/m³
Nunavut	OEL TWA (ppm)	10 ppm
Northwest Territories	OEL STEL (mg/m³)	39 mg/m ³
Northwest Territories	OEL STEL (ppm)	15 ppm
Northwest Territories	OEL TWA (mg/m³)	26 mg/m³
Northwest Territories	OEL TWA (ppm)	10 ppm
Ontario	OEL STEL (ppm)	15 ppm
Ontario	OEL TWA (ppm)	10 ppm
Prince Edward Island	OEL STEL (ppm)	15 ppm
Prince Edward Island	OEL TWA (ppm)	10 ppm
Québec	VECD (mg/m³)	37 mg/m³
Québec	VECD (ppm)	15 ppm
Québec	VEMP (mg/m³)	25 mg/m³
Québec	VEMP (ppm)	10 ppm
Saskatchewan	OEL STEL (ppm)	15 ppm
Saskatchewan	OEL TWA (ppm)	10 ppm
Yukon	OEL STEL (mg/m³)	43 mg/m³
Yukon	OEL STEL (ppm)	25 ppm
Yukon	OEL TWA (mg/m³)	25 mg/m³
Yukon	OEL TWA (ppm)	10 ppm

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Ensure all national/local regulations are observed.

Personal Protective Equipment: Gloves. Protective clothing. Protective goggles.







Materials for Protective Clothing: Chemically resistant materials and fabrics.

Hand Protection: Wear chemically resistant protective gloves.

Eye Protection: Chemical goggles or safety glasses.

Skin and Body Protection: Wash contaminated clothing before reuse.

Respiratory Protection: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed

established Occupational Exposure Limits.

Other Information: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties
Physical State : Liquic

Appearance : Tan. Base: Red, Hardener: White

Odor Clove-like **Odor Threshold** Not available Not available pН **Evaporation Rate** Not available Freezing/Melting Point Not available **Boiling Point** Not available **Flash Point** Not available **Auto-ignition Temperature** Not available Not available **Decomposition Temperature** Flammability (solid, gas) Not available **Upper/Lower Flammable Limit** Not available

09/16/2014 EN (English US) 6/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Vapor Pressure: Not availableRelative Vapor Density at 20 °C: Not available

Specific Gravity : 1 - 3

Solubility : Not soluble in water

Partition Coefficient: N-octanol/water: Not availableViscosity: Not available

Explosion Data – Sensitivity to Mechanical Impact : Not expected to present an explosion hazard due to mechanical impact. Explosion Data – Sensitivity to Static Discharge : Not expected to present an explosion hazard due to static discharge.

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: The product is stable at normal handling and storage conditions.

<u>Possibility of Hazardous Reactions</u>: Hazardous polymerization will not occur.

Conditions to Avoid: Extremely high or low temperatures. Sources of ignition. Incompatible materials.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Hazardous Decomposition Products: None known.

SECTION 11: TOXICOLOGICAL INFORMATION

Information on Toxicological Effects - Product

Acute Toxicity: Not classified LD50 and LC50 Data: Not available

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage/Irritation: Causes serious eye irritation.

Respiratory or Skin Sensitization: May cause an allergic skin reaction.

Germ Cell Mutagenicity: Not classified

Teratogenicity: Not available **Carcinogenicity:** Not classified

Specific Target Organ Toxicity (Repeated Exposure): May cause damage to organs through prolonged or repeated exposure.

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified

Aspiration Hazard: Not classified

Symptoms/Injuries After Inhalation: May cause respiratory irritation. Inhalation of fumes may cause metal fume fever.

Symptoms/Injuries After Skin Contact: Causes skin irritation. May cause an allergic skin reaction.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: Ingestion is likely to be harmful or have adverse effects.

Chronic Symptoms: The chronic effects of this substance are unknown.

Information on Toxicological Effects - Ingredient(s)

LD50 and LC50 Data:

Zinc oxide (1314-13-2)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg
Eugenol (97-53-0)	
LD50 Oral Rat	1930 mg/kg
Petrolatum (8009-03-8)	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rat	> 2000 mg/kg read across
LD50 Dermal Rabbit	3600 mg/kg
Paraffin waxes and Hydrocarbon waxes (8002-74-2)	
LD50 Oral Rat	> 3750 mg/kg
LD50 Dermal Rabbit	> 3600 mg/kg
Acetic acid (64-19-7)	
LD50 Oral Rat	3310 mg/kg
LD50 Dermal Rabbit	1060 μl/kg
LC50 Inhalation Rat	11.4 mg/l/4h

09/16/2014 EN (English US) 7/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Talc (14807-96-6)	
IARC Group 3	
National Toxicity Program (NTP) Status Evidence of Carcinogenicity, Twelfth Report - Items under consideration.	
Eugenol (97-53-0)	
IARC Group	3

SECTION 12: ECOLOGICAL INFORMATION

Toxicity

Ecology - General: Very toxic to aquatic life. Very toxic to aquatic life with long lasting effects.

Ecology - General: Very toxic to aquatic line. Very toxic to aquatic line with long lasting effects.		
Zinc oxide (1314-13-2)		
780 μg/l (Exposure time: 96 h - Species: Pimephales promelas)		
0.122 mg/l		
0.026 mg/l (Species: Jordanella floridae)		
> 100 g/l (Exposure time: 96 h - Species: Brachydanio rerio [semi-static])		
Petrolatum (8009-03-8)		
> 1000 mg/l LLO; insoluble in water		
> 1000 mg/l		
Acetic acid (64-19-7)		
79 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])		
65 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])		
75 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])		

Persistence and Degradability

KELLY'S® Z.O.E. IMPRESSION PASTE	
Persistence and Degradability	Not established. May cause long-term adverse effects in the environment.

Bioaccumulative Potential

KELLY'S® Z.O.E. IMPRESSION PASTE	
Bioaccumulative Potential	Not established.
Talc (14807-96-6)	
BCF Fish 1	(no known bioaccumulation)
Petrolatum (8009-03-8)	
Log Pow	> 6 Calculated
Acetic acid (64-19-7)	
Log Pow	-0.31 (at 20 °C)

Mobility in Soil Not available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, provincial, territorial and international regulations.

Ecology - Waste Materials: This material is hazardous to the aquatic environment. Keep out of sewers and waterways.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT

Packing Group

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCES, LIQUID, N.O.S. (Contains Zinc Oxide)

Hazard Class : 9

Identification Number: UN3082Label Codes: 9

Marine Pollutant : Marine pollutant

ERG Number : 171

: 111

09/16/2014 EN (English US) 8/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

In Accordance with IMDG

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Zinc Oxide)

Hazard Class : 9

Identification Number : UN3082

Packing Group: IIILabel Codes: 9EmS-No. (Fire): F-AEmS-No. (Spillage): S-F

Marine pollutant : Marine pollutant

In Accordance with IATA

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Zinc Oxide)

Packing Group : III

Identification Number : UN3082

Hazard Class: 9Label Codes: 9ERG Code (IATA): 9L

In Accordance with TDG

Proper Shipping Name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Contains Zinc Oxide)

Packing Group : III
Hazard Class : 9
Identification Number : UN3082

Label Codes : 9

Marine Pollutant (TDG) : Marine pollutant

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

KELLY'S® Z.O.E. IMPRESSION PASTE		
	SARA Section 311/312 Hazard Classes	Immediate (acute) health hazard

Zinc oxide (1314-13-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Rosin, polymerized (65997-05-9)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Talc (14807-96-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Cottonseed oil (8001-29-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

Eugenol (97-53-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Fatty acids, linseed-oil (68424-45-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

EPA TSCA Regulatory Y2 - Y2 - indicates an exempt polymer that is a polyester and is made only from reactants included in a specified list of low concern reactants that comprises one of the eligibility criteria for the exemption rule.

Petrolatum (8009-03-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Paraffin waxes and Hydrocarbon waxes (8002-74-2)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Olive oil (8001-25-0)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

09/16/2014 EN (English US) 9/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Acetic acid (64-19-7)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

US State Regulations

Zinc oxide (1314-13-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Talc (14807-96-6)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Cottonseed oil (8001-29-4)

U.S. - Pennsylvania - RTK (Right to Know) List

Paraffin waxes and Hydrocarbon waxes (8002-74-2)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) List

Acetic acid (64-19-7)

- U.S. Massachusetts Right To Know List
- U.S. New Jersey Right to Know Hazardous Substance List
- U.S. Pennsylvania RTK (Right to Know) Environmental Hazard List
- U.S. Pennsylvania RTK (Right to Know) List

Canadian Regulations

KELLY'S® Z.O.E. IMPRESSION PASTE

WHMIS Classification Class D Division 2 Subdivision B - Toxic material causing other toxic effects



Zinc oxide (1314-13-2)

Listed on the Canadian DSL (Domestic Sustances List), Listed on the Canadian IDL (Ingredient Disclosure List)

IDL Concentration 1 %

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Rosin, polymerized (65997-05-9)

Listed on the Canadian DSL (Domestic Sustances List)

Talc (14807-96-6)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Class D Division 2 Subdivision A - Very toxic material causing other toxic effects

Cottonseed oil (8001-29-4)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

Eugenol (97-53-0)

Listed on the Canadian DSL (Domestic Sustances List)

Fatty acids, linseed-oil (68424-45-3)

Listed on the Canadian DSL (Domestic Sustances List)

Petrolatum (8009-03-8)

Listed on the Canadian DSL (Domestic Sustances List)

WHMIS Classification Uncontrolled product according to WHMIS classification criteria

09/16/2014 EN (English US) 10/11

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Paraffin waxes and Hydrocarbon waxes (8002-74-2)			
Listed on the Canadian DSL (D	Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria		
Olive oil (8001-25-0)			
Listed on the Canadian DSL (D	Listed on the Canadian DSL (Domestic Sustances List)		
WHMIS Classification	Uncontrolled product according to WHMIS classification criteria		
Acetic acid (64-19-7)			
Listed on the Canadian DSL (Domestic Sustances List), Listed on the Canadian IDL (Ingredient Disclosure List)			
IDL Concentration 1 %			
WHMIS Classification	Class B Division 3 - Combustible Liquid		
	Class E - Corrosive Material		

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 09/16/2014

Other Information : This document has been prepared in accordance with the SDS requirements of the OSHA

Hazard Communication Standard 29 CFR 1910.1200.

GHS Full Text Phrases:

Acute Tox. 4 (Oral)	Acute toxicity (oral) Category 4
Aquatic Acute 1	Hazardous to the aquatic environment - Acute Hazard Category 1
Aquatic Acute 3	Hazardous to the aquatic environment - Acute Hazard Category 3
Aquatic Chronic 1	Hazardous to the aquatic environment - Chronic Hazard Category 1
Comb. Dust	Combustible Dust
Eye Dam. 1	Serious eye damage/eye irritation Category 1
Eye Irrit. 2A	Serious eye damage/eye irritation Category 2A
Flam. Liq. 3	Flammable liquids Category 3
Skin Corr. 1A	Skin corrosion/irritation Category 1A
Skin Irrit. 2	Skin corrosion/irritation Category 2
Skin Sens. 1	Skin sensitization Category 1
STOT RE 2	Specific target organ toxicity (repeated exposure) Category 2
H226	Flammable liquid and vapor
Comb. Dust	May form combustible dust concentrations in air
H302	Harmful if swallowed
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H402	Harmful to aquatic life
H410	Very toxic to aquatic life with long lasting effects

Party Responsible for the Preparation of This Document

Water Pik, Inc.

Telephone: 800-525-2020

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

North America GHS US 2012 & WHMIS 2

09/16/2014 EN (English US) 11/11