

1 Identification of the substance/mixture and of the company/undertaking

- **Product identifier**
- **Trade name:** ALLOY PRIMER
- **Article number:** US054
- **Application of the substance / the preparation** Adhesive, dental metal
- **Details of the supplier of the safety data sheet**
- **Manufacturer:**
Kuraray Noritake Dental Inc.
1621 Sakazu, Kurashiki, Okayama 710-0801,
Japan
- **Contact information:**
Kuraray America, Inc.
33 Maiden Lane, 6th Floor, New York,
NY 10038 U.S.A.
Tel: 800-879-1676
Fax: 888-700-5200
Website: www.kuraraydental.com

2 Composition/information on ingredients

- **Chemical characterization: Mixtures**
- **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

67-64-1	acetone	H225; H319; H336	>90%
---------	---------	-------------------	------

- **Other ingredients:**
6-(4-Vinylbenzyl-N-propyl)amino-1,3,5-triazine-2,4-dithione
10-Methacryloyloxydecyl dihydrogen phosphate

3 Hazards identification

· **Classification of the substance or mixture**



GHS02 Flame

H225 Highly flammable liquid and vapour.



GHS07

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Classification according to Directive 67/548/EEC or Directive 1999/45/EC**



Irritant

Irritating to eyes.



Highly flammable

Highly flammable.

Vapours may cause drowsiness and dizziness.

· **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of international guidelines.

· **Classification system:**

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

(Contd. on page 2)

Trade name: ALLOY PRIMER

(Contd. of page 1)

· **Label elements**

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonized System (GHS).

· **Hazard pictograms** GHS02, GHS07

· **Signal word** Danger

· **Hazard statements**

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P241 Use explosion-proof electrical/ventilating/lighting/equipment.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

· **HMIS-ratings (scale 0 - 4)**



Health = 1

Fire = 3

Reactivity = 0

4 First aid measures

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Generally the product does not irritate the skin.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:**

Do not induce vomiting; immediately call for medical help.

If symptoms persist consult doctor.

5 Firefighting measures

· **Suitable extinguishing agents:**

CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Protective equipment:**

Wear self-contained respiratory protective device.

Wear fully protective suit.

Trade name: ALLOY PRIMER

(Contd. of page 2)

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Ensure adequate ventilation.
- **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.
- **Information about protection against explosions and fires:**
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location (2-25°C).
- **Information about storage in one common storage facility:**
Store away from oxidizing agents.
Store away from reducing agents.
- **Further information about storage conditions:**
Keep receptacle tightly sealed.
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see item 7.

· **Components with limit values that require monitoring at the workplace:**

67-64-1 acetone

PEL	2400 mg/m ³ , 1000 ppm
REL	590 mg/m ³ , 250 ppm
TLV	Short-term value: 1782 mg/m ³ , 750 ppm Long-term value: 1188 mg/m ³ , 500 ppm
	BEI

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Personal protective equipment:**
- **General protective and hygienic measures:**
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes.
- **Breathing equipment:** Use suitable respiratory protective device in case of insufficient ventilation.

(Contd. on page 4)

Trade name: ALLOY PRIMER

(Contd. of page 3)

· **Protection of hands:**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

· **Appearance:**

Form: Liquid
Color: Transparent
Odor: Acetone-like

· **pH-value:** Not applicable

· **Change in condition**

Melting point/Melting range: 94.7 °C (acetone)
Boiling point/Boiling range: 55°C (131 °F) (acetone)

· **Flash point:** -19°C (-2 °F) (acetone)

· **Ignition temperature:** 465.0°C (869 °F) (acetone)

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapor mixtures are possible.

· **Explosion limits:**

Lower: 2.6 Vol % (acetone)
Upper: 13.0 Vol % (acetone)

· **Vapor pressure at 20°C (68 °F):** 233.0 hPa (175 mm Hg) (acetone)

· **Density:** 0.79 g/cm³ (acetone)
· **Vapour density** 2.0 g/cm³ (acetone, air=1)

· **Solubility in / Miscibility with**

Water: Partly miscible.

· **Segregation coefficient (n-octanol/water):** -0.24 (acetone)

· **VOC content:** 99.0 %

· **Other information** No further relevant information available.

Printing date 05/01/2016

Reviewed on 05/01/2016

Trade name: ALLOY PRIMER

(Contd. of page 4)

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:**
No decomposition if used and stored according to specifications.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** Carbon monoxide and carbon dioxide

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values that are relevant for classification:**

67-64-1 acetone

Oral	LD50	5800 mg/kg (rat)
Dermal	LD50	20000 mg/kg (rabbit)

- **Primary irritant effect:**
- **on the skin:** No irritant effect.
- **on the eye:** Irritating effect.
- **Sensitization:** No sensitizing effects known.
- **Additional toxicological information:**
The product shows the following dangers according to internally approved calculation methods for preparations:
Irritant

12 Ecological information

- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Water hazard class 1 (Self-assessment): slightly hazardous for water
Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.



14 Transport information

· UN-Number	
· DOT	UN1090
· ADR, IMDG, IATA	1090
· UN proper shipping name	
· ADR	1090 ACETONE, solution

(Contd. on page 6)

Trade name: ALLOY PRIMER

(Contd. of page 5)

· IMDG, IATA	ACETONE, solution
· Transport hazard class(es)	
· DOT, IMDG, IATA	
	
· Class	3 Flammable liquids.
· Label	3
<hr style="border-top: 1px dashed #000;"/>	
· ADR	
	
· Class	3 Flammable liquids
· Label	3
· Packing group	
· DOT, ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids
· Danger code (Kemler):	33
· EMS Number:	F-E,S-D
· Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code	Not applicable.
· UN "Model Regulation":	UN1090; ACETONE, solution; 3; II

15 Regulatory information

· **Sara**

· **Section 355 (extremely hazardous substances):**

None of the ingredient is listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients is listed.

· **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

· **Proposition 65**

· **Chemicals known to cause cancer:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients is listed.

· **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients is listed.

· **Chemicals known to cause developmental toxicity:**

None of the ingredients is listed.

(Contd. on page 7)

Printing date 05/01/2016

Reviewed on 05/01/2016

Trade name: ALLOY PRIMER

(Contd. of page 6)

· **Carcinogenicity categories**

· EPA (Environmental Protection Agency)	
67-64-1 acetone	I

· IARC (International Agency for Research on Cancer)	
None of the ingredients is listed.	

· TLV (Threshold Limit Value established by ACGIH)	
67-64-1 acetone	A4

· NIOSH-Ca (National Institute for Occupational Safety and Health)	
None of the ingredients is listed.	

· OSHA-Ca (Occupational Safety & Health Administration)	
None of the ingredients is listed.	

· **GHS label elements** Not determined

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Version:** 4

· **Relevant phrases**

- Not applicable
- H225 Highly flammable liquid and vapour.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.